LAW OFFICES
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 PENNSYLVANIA AVENUE, N.W.
WASHINGTON, DC 20037-3213
TELEPHONE (202) 293-7060
FACSIMILE (202) 293-7860
www.sughrue.com

JC535 U.S. PTO
10/20/00

JC806 U.S. PTO
09/692045
10/20/00

October 20, 2000

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Re: Application of Kenji KIRA, Lee CHIEN HUI, Teruyoshi NUMATA
IMAGE PROCESSING APPARATUS
Our Ref. Q61394

Dear Sir:

Attached hereto is the application identified above including 29 sheets of the specification, claims, 10 sheet(s) of informal drawings, executed Assignment and PTO 1595 form, Information Disclosure Statement, PTO Form 1449 and executed Declaration and Power of Attorney.

The Government filing fee is calculated as follows:

Total claims	5	-	20	=		x	$18.00	=	$.00
Independent claims	4	-	3	=	1	x	$80.00	=	$80.00
Base Fee									$710.00
TOTAL FILING FEE									**$790.00**
Recordation of Assignment									$40.00
TOTAL FEE									**$830.00**

Checks for the statutory filing fee of $790.00 and Assignment recordation fee of $40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16 and 1.17 and any petitions for extension of time under 37 C.F.R. § 1.136 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from October 20, 1999 based on Japanese Application No. P.Hei. 11-298631. The priority document(s) will be filed at a later date.

Respectfully submitted,
SUGHRUE, MION, ZINN,
MACPEAK & SEAS, PLLC
Attorneys for Applicant

By: Registration No. 32,778
Darryl Mexic
Registration No. 23,063

DM/amt

IMAGE PROCESSING APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to image processing, particularly to an image processing apparatus which can be used as an "electronic makeup" apparatus providing high quality and natural looking images in a field where sophisticated works are required in both the contents and representation, such as television dramas and movies.

2. Description of the Related Art

It is known that by applying a two-dimensional ε-filter (for example, refer to Harajima and others "ε-Separating Nonlinear Digital Filter and Its Applications" IEICE (The Institute of Electronics, Information and Communication Engineers) 1982, 4,J65-A, No.4, pp297-304) to an image of a human face, neck, hand, etc., a "smooth skin" image with wrinkles and spots removed or decreased can be obtained (refer to Arakawa and others "Color Face Image Processing by Vector ε-Filter ~ Removal of Wrinkles~" March 1998, 1998 General Conference of IEICE D-11-143, PP143-). This will be hereinafter referred to as conversion to "smooth skin." This is based on the fact that small-amplitude light and dark change is smoothed by "separating and suppressing small-amplitude high-frequency noise components in an image", which is a function of the

two-dimensional ε-filter.

The ε-filter was originally designed for the purpose of separating and removing the small-amplitude high-frequency noise components superimposed on a signal waveform.

A low-pass filter (LPF) that is usually used for noise removal not only suppresses noise components, but also degrades edges of signals. Thus if it is applied to an image, the low-pass filter has the disadvantage of blurring the whole image. However, as shown in the relationship between the input and output signals of the ε-filter in FIG. 1, the ε-filter has a characteristic of flattening only small-amplitude level changes in a signal waveform, and has a feature of scarcely impairing sharpness of the whole image because the edges which have steep level changes are preserved.

Letting an input signal sequence be x (m, n), the output signal y (m, n) of the two-dimensional ε-filter is represented by the following expression (1):

$$y(m, n) = x(m, n) - \sum_{i} \sum_{j} a_{i,j} \cdot F\big(x(m, n) - x(m+i, n+j)\big) \qquad (1)$$

where $a_{i,j}$ is a weight coefficient. If the filter size is (2M+1) X (2N+1), it will satisfy the following expression:

$$\sum_{i=-M}^{M}\sum_{j=-N}^{N} a_{i,j} = 1 \qquad (2)$$

The function F(x) represented in expression (1) is a nonlinear function shown in a graph of FIG. 2 and F(x)=0 when $|X|>\varepsilon_o$.

Throughout the specification, the value of ε_o will be referred to as ε value.

FIG. 3 shows a basic configuration of the two-dimensional ε-filter.

In FIG. 3, the solid line frame denoted by numeral 1 indicates a calculation section of a small-amplitude high-frequency noise component u (m, n) (the second term on the right side in expression (1)). Output from the calculation section is subtracted from the input signal sequence x (m, n), whereby the output signal sequence y (m, n) with the small-amplitude noise component suppressed is provided.

By applying ε-filter to an image of a human face, the face image can be converted into a beautiful face having "smooth skin" with wrinkles and spots removed or decreased. The wrinkles and spots are not so-called noise, but involve comparatively small-amplitude light and dark changes in an image. The wrinkles and spots can be made inconspicuous, by smoothing these small-amplitude light and dark changes with the small-amplitude level change suppressing function of the

ε-filter.

Here, only the small-amplitude level changes such as the wrinkles and spots are flattened and steep level changes such as boundaries of pupils, eyelids, eyebrows, etc., are kept, so that sharpness of the whole image is scarcely impaired and conversion to "smooth skin" can be accomplished.

Conversion to "smooth skin" is intended for skin areas strictly. However, if the whole image is processed uniformly through the ε filter, small-amplitude level changes of peripheral images are also suppressed and as a result, delicate light and dark patterns of hairs, clothes, backgrounds, etc., are also flattened, resulting in an image where original details and texture are impaired.

This is fatal in applications wherein high quality is demanded for the whole image such as television, movies, etc. However, the ε filter is made to selectively act only on the skin color area of an image, whereby conversion to "smooth skin" can be accomplished without impairing any details or texture of peripheral images. To do this, a technique called "chromakey" (technique of electronically discriminating a specific color area in an image from others and applying image processing such as filtering only to the area restrictedly), a well-used device in the television technical field, may be adopted.

As described above, conversion to "smooth skin" through

the ε filter has the potential for use as "electronic makeup" in television drama and movie production, etc. However, to make the most of the ε filter in the field where there are various demands for image processing and requirements for high quality of the whole image, the following problems to be resolved exist:

Conversion to "smooth skin" makes a skin image seem to be smooth, and thus also produces the "rejuvenation" effect as video representation. For an elderly actress to act as a girl such as in a drama of a biography, etc., although there are existing points to be improved (which will be pointed out later), conversion to "smooth skin" is a promising technique to be used as an electronic makeup technique where "rejuvenating skin" is obtained by performing image processing.

As described above, conversion to "smooth skin" can be realized using the ε filter. On the other hand, for playing an aged person drastically exceeding the actual age such as in a television drama or a movie, an electronic makeup technique for producing an "old" effect such as "wrinkle enhancement" is also demanded. However, hitherto, it has been impossible to realize "wrinkle enhancement" which can also be said to be the opposite effect to conversion to "smooth skin."

In conversion to "smooth skin" using the ε filter, the degree (strength) of conversion to "smooth skin" can be easily adjusted simply by changing one parameter (ε_o in FIG. 2) in response to the strength of the wrinkles and spots to be hidden.

Although the whole skin becomes smooth as the degree of conversion to "smooth skin" is increased, the grain and texture of the skin are lost and "plastic" texture rather than "human skin" results, leading to an image poor in reality. To avoid this, if conversion to "smooth skin" is weakened, the natural look is recovered, but the wrinkles and spots to be hidden appear; this is a dilemma.

In other words, a solution to "provide an image where the grain and texture of the skin are preserved while hiding annoying wrinkles and spots" becomes necessary.

Further, assuming that the above-described "wrinkle enhancement" can be realized, it is desired to provide a "wrinkles enhanced" image with the grain of the skin kept in the original state rather than simple "wrinkle enhancement," needless to say.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to realize "wrinkle enhancement" that was previously impossible, and to provide an image processing apparatus for performing conversion to "smooth skin" without impairing the grain or texture of skin, and "wrinkle enhancement" with the grain of the skin preserved in its original state.

Finally, according to the invention, an image processing apparatus is provided for performing conversion to "smooth skin"

or "wrinkle enhancement" for an input image. This apparatus is characterized by input image signals which are applied to an input terminal of a ε -filter, and an extended ε -filter adapted to extract selectively or simultaneously, "wrinkle enhanced" signals obtained by adding the output signal of a small amplitude variation component calculation section of the ε -filter to the input image signal, and "smooth skin" converted signals of the input image signals (which is the output of the previously mentioned ε - filter).

According to this invention, an image processing apparatus is provided, which is characterized by having the ability to extract an input image signal as a "smooth skin" converted signal while preserving the grain and texture of the skin. This is achieved by applying an input image signal to input terminals of two ε-filters having large and small ε values, and adding the output signal of the small-amplitude variation component calculation section of the smaller ε valued ε-filter to the output signal of the ε-filter having the larger ε value.

According to this invention, an image processing apparatus is provided, which is characterized by having the ability to get an image signal as a "smooth skin" converted signal or a "wrinkle enhanced" signal correspondingly, while preserving the grain and texture of the skin. This is achieved by applying an input image signal to the input terminal of a large ε valued extended ε-filter and the input terminal of a

small ε valued ε-filter. When the correction instruction is "smooth skin" conversion, a "smooth skin" converted signal preserving the grain and texture of the skin is obtained by adding the output signal of the small-amplitude variation component calculation section of the ε-filter to the "smooth skin" converted output signal of the extended ε-filter.

When the correction instruction is "wrinkle enhancement", a "wrinkle enhanced" signal preserving the grain and texture of the skin by subtracting the output signal of the small-amplitude variation component calculation section of the ε-filter from the "wrinkle enhancement" output signal of the extended ε-filter.

According to the invention, an image processing apparatus is provided, which is characterized by having the ability to selectively or simultaneously provide

a "smooth skin" converted signal preserving the grain and texture of the skin,

a "wrinkle enhanced" signal keeping the grain and texture of a skin in its original state. This is achieved by a new type digital filter (named "β-filter") which separates specific variation components within a specified amplitude band. When given any two large and small amplitude values that can be set arbitrarily, the β-filter selectively separates only the variation components which have an amplitude value between the two given amplitude values.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the characteristic of a ε-filter based on the relationship between the input signal and the output signal.

FIG. 2 is a graph of the nonlinear function F(X) used in the ε-filter.

FIG. 3 shows the basic configuration of a two-dimensional ε-filter.

FIG. 4 shows a configuration example of the invented image processing apparatus executing conversion to "smooth skin" and "wrinkle enhancement" in "one-output type".

FIG. 5 shows a configuration example of the invented image processing apparatus executing conversion to "smooth skin" and "wrinkle enhancement" in "continuously parallel output type".

FIG. 6 shows a configuration example of the invented image processing apparatus intended for "removing annoying wrinkles and spots with the grain and texture of the skin, the smaller variation, preserved".

FIG. 7 shows a configuration example of the invented image processing apparatus for selectively performing processing of "removing annoying wrinkles and spots with the grain and texture of the skin, the smaller variation, preserved" and "enhancing significant wrinkles and spots while preserving the grain and texture of the skin in its original state".

FIG. 8 is a graph to show the nonlinear function φβL,

βh (X) which defines the newly invented digital filter (β filter).

FIG. 9 shows that by using only one β-filter, high-quality conversion to "smooth skin" and "wrinkle enhancement" preserving the grain and texture of the original skin image can be achieved.

FIG. 10 shows a configuration example of the invented "one-output type" β-filter, image processing apparatus, for executing conversion to "smooth skin" and "wrinkle enhancement" preserving the grain and texture of the original skin image.

FIG. 11 shows a configuration example of the invented "simultaneously output type" β-filter, image processing apparatus, for executing conversion to "smooth skin" and "wrinkle enhancement" preserving the grain and texture of the original skin image.

FIG. 12 shows a configuration example of an "electronic makeup" apparatus, which is configured by combining a β-filter and a color area determination circuit.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

Referring now to the attached drawings, the preferred embodiments of the invention are shown.

The invention will be discussed in the following order:

(1) Realization of "wrinkle enhancement"

(2) Realization of conversion to "smooth skin" and "wrinkle enhancement" while preserving the grain and texture of the skin

The filter according to the invention, which is capable of providing both functions of "smooth skin" and "wrinkle enhancement" conversion, will be hereinafter referred to as extended ε-filter.

Item (2) above is realized by the following three methods a to c:

a. Two ε-filters represented by expression (1) are used in combination to execute conversion to "smooth skin" with a natural look.

b. An ε-filter and an extended ε-filter are used in combination in order to execute switch-able conversion to "smooth skin" and "wrinkle enhancement" with a natural look.

c. A new digital filter provided by the invention is used to execute conversion to "smooth skin" and "wrinkle enhancement" with a natural look.

First, realization of "wrinkle enhancement" in (1) will be discussed.

It is difficult to make a new wrinkle at a point where no wrinkle exists. In this invention, the output of the small-amplitude variation component calculation section, which is a component of the ε-filter, is used to enhance an original wrinkle.

To execute conventional conversion to "smooth skin", the small-amplitude variation component calculation section, indicated by numeral 1 in the ε-filter, finds the small-amplitude

variation component of an input signal sequence and the component is subtracted from the input signal sequence (see FIG. 3).

Conversely, as shown in expression (3), the small-amplitude variation component (second term on the right side of expression (3)) is added to the input signal sequence (first term on the right side), whereby the small-amplitude variation component of a wrinkle, etc., can be enhanced ("wrinkle enhancement"). However, the addition (same phase addition) result might exceed the stipulated level range of a digital image (for example, 0 to 255 in 8 bits range), thus clip processing after addition (processing of limiting the result to 0 if the result is 0 or less and limiting the result to 255 if the result is 255 or more) is required.

$$y(m,n) = x(m,n) + \sum_{i}\sum_{j} a_{i,j} \cdot F\left(x(m,n) + x(m+i,n+j)\right) \qquad (3)$$

It is convenient and cost efficient to integrate the apparatus for realizing "wrinkle enhancement" with the existing apparatus for realizing conversion to "smooth skin", and enable both conversion to "smooth skin" and "wrinkle enhancement."

As the integral circuit configuration, the following two configurations are possible:

(a) Configuration wherein either "smooth skin" or "wrinkle enhancement" conversion signal is output (which will be

hereinafter referred to as "one-output type"), and the small-amplitude variation components are added / subtracted to / from the input image in response in to an external conversion instruction (="smooth skin"/ "wrinkle enhancement") and

(b) configuration wherein the processed results of conversion to "smooth skin" and "wrinkle enhancement" are output simultaneously, which will be hereinafter referred to as "simultaneous output type," and either can be selected for use as required.

(both configurations will be referred to as extended ε-filters throughout the specification.)

FIGS. 4 and 5 show configuration examples of the invented image processing apparatus for executing conversion to "smooth skin" and "wrinkle enhancement" in the forms corresponding to (a) and (b) above. In FIGS. 4 and 5, the portion of the solid line frame indicated by numeral 1 is a calculation section of a small-amplitude variation component U (m, n). A conversion instruction section indicated by numeral 2 in FIG. 4 is a section for instructing the image processing apparatus to perform either conversion to "smooth skin" or "wrinkle enhancement." Each apparatus comprises a clip circuit (Clip) for suppressing the addition (same phase addition) result of the small-amplitude variation component for "wrinkle enhancement" to the stipulated level range of a digital image (for example, 0 to 255).

Next, the method of realizing conversion to "smooth skin" while preserving the grain and texture of the skin by using two ε-filters represented by expression (1) in combination (the method in (2) a. described above) will be discussed.

First, the principle will be discussed.

A wrinkle, a spot, and grain of the skin are all comparatively small-amplitude level changes (amplitude variation). However, if a wrinkle and a spot at an annoying level are compared with the grain of the skin, generally the amplitude variation of the grain of the skin is comparably minute. So-called image pickup noise is a possible variation element close to the amplitude variation of the grain of the skin, but the image pickup noise may be ignored in high-quality image pick-up conditions of television and movies.

In other words, there is the following relationship among them:

Amplitude variation of wrinkles or spots > amplitude variation of grains and textures of skin >> image pickup noise

Incidentally, if a small amplitude value εh adequate for removing wrinkles and spots (conversion to "smooth skin") is processed as the ε value (see FIG. 2) through the ε-filter represented by expression (1), the level change concerning the grain of the skin will, of course, also be suppressed.

On the other hand, according to the operation principle of the ε-filter, the minute-amplitude variation component u

(m, n), provided by setting a minute amplitude value εL (εL<εh) as the ε value (which matches the amplitude variation for the grain of the skin), and processing it through the ε-filter, is a level change related to the grain and texture of the skin. Therefore, in the invention, it is used to revive the grain and texture of the skin which was lost in previous technique.

In other words, in order to "preserve the grain of the skin with smaller variation width while removing annoying wrinkles and spots (conversion to "smooth skin"),"

(a) the original image is converted to "smooth skin" using a small amplitude value εh through ε-filter I (here, the grain component is also suppressed);

(b) the level variation component with minute amplitude (grain component) is separated from the original image using the minute amplitude value εL through ε-filter II; and

(c) the level variation component with minute amplitude separated in (b) is added to the processing result of the "smooth skin" conversion in (a).

FIG. 6 shows a configuration example of the invented image processing apparatus for performing the signal processing described above.

Next, the method in (2) b. described above will be discussed, namely, the method of using extended ε-filter I and ε-filter II in combination in order to realize switch-able conversion to "smooth skin" and "wrinkle enhancement" with a natural look.

Also in this method, in order to execute conversion to "smooth skin," the minute-amplitude variation component u (m, n), provided through the ε-filter II, is added to output of the extended ε-filter I as explained in the method (2) a. described above. Thus the grain and texture of the skin which had been lost in previous technique is revived

In contrast, in order to execute "wrinkle enhancement," enhancement of the grain based on the minute-amplitude variation component u (m, n), which is essentially undesirable, is canceled for restoring the original grain level.

In other words, in order to "enhance significant wrinkles and spots while preserving the grain of the skin in its original state,"

(a) wrinkles of an original image are enhanced according to small amplitude value εh, by using extended ε-filter I (here, the grain component is also enhanced);

(b) level variation component with minute amplitude (grain component) is separated from the original image, using the minute amplitude value εL through the ε-filter II; and

(c) the level variation component with minute amplitude separated in (b) is subtracted from the processing result of "wrinkle enhancement" in (a).

FIG. 7 shows a configuration example of the invented image processing apparatus, for selectively performing processing between "preserving the grain of the skin, which has smaller

variation width, while removing annoying wrinkles and spots" and "enhancing significant wrinkles and spots while preserving the grain of the skin in its original state."

In FIG. 7, a minute amplitude component adjustment section, indicated by numeral 3, is a section for performing adjustment processing of a minute amplitude variation component. This section is for executing the algorithm of the minute amplitude variation component u2 (m, n), which is separated through the ε-filter II for output y1 (m, n) of the extended ε-filter I, in response to the correction instruction for conversion to "smooth skin" or "wrinkle enhancement" (addition if the instruction is conversion to "smooth skin" or subtraction if the instruction is "wrinkle enhancement").

In this case, the extended ε-filter I is provided for performing conversion to "smooth skin" or "wrinkle enhancement" in accordance with the correction instruction; this topic was previously described with reference to FIG. 6.

Next, the method in (2) c. described above, will be discussed. This is the method to realize conversion to "smooth skin" and "wrinkle enhancement" with a natural look by using a new digital filter provided by the invention.

First, the method in (2) a. described above, will be reviewed. This is the method of using two ε-filters in combination, represented by expression (1), in order to perform conversion to "smooth skin" with a natural look. This method is executed

according to the configuration previously described with reference to FIG. 6.

Signal processing performed according to the configuration in FIG. 6 is represented by expression (4). In expression (4), the first term on the right side (enclosed in braces) indicates the function of the ε-filter I (conversion to "smooth skin" based on ε=εh). The second term on the right side following the first term indicates the function of the ε-filter II (separation of the variation component "related to the grain of the skin" of amplitude ε or less).

$$y(m,n)=\left\{x(m,n)-\sum_{i}\sum_{j}a_{i,j}\cdot F_{\varepsilon h}\left(x(m,n)-x(m+i,n+j)\right)\right\}+\sum_{i}\sum_{j}a_{i,j}\cdot F_{\varepsilon L}\left(x(m,n)-x(m+i,n+j)\right)$$

..... (4)

Now, if expression 4 is sorted out by focusing attention on:

$$\sum_{i}\sum_{j}a_{i,j}$$

the following expression (5) is obtained.

$$y(m,n)=x(m,n)-\sum_{i}\sum_{j}a_{i,j}\cdot\left\{F_{\varepsilon h}\left(x(m,n)-x(m+i,n+j)\right)-F_{\varepsilon L}\left(x(m,n)-x(m+i,n+j)\right)\right\}$$

..... (5)

The Fε (X) (see FIG. 2) returns the same value for x with

$|X| \leq \varepsilon$, otherwise it returns 0. Thus, $F\varepsilon h\ (\Delta x)$ and $F\varepsilon L\ (\Delta x)$ becomes the following:

When $|\Delta x| \leq \varepsilon L$, $F\varepsilon h\ (\Delta x) = \Delta x$, $F\varepsilon L\ (\Delta x) = \Delta x$

when $\varepsilon L < |\Delta x| \leq \varepsilon h$, $F\varepsilon h\ (\Delta x) = \Delta x$, $F\varepsilon L\ (\Delta x) = 0$

when $\varepsilon L < |\Delta x|$, $F\varepsilon h\ (\Delta x) = 0$, $F\varepsilon L\ (\Delta x) = 0$

Therefore, the whole portion represented by $\{F\varepsilon h\ (\Delta x) - F\varepsilon L\ (\Delta x)\}$ in expression 5 has a characteristic of outputting the same value only for the variation component Δx contained in the amplitude band with $\varepsilon L < |\Delta x| \leq \varepsilon h$, and otherwise outputting 0.

This characteristic indicates a new nonlinear function defined by two parameters βL and βh as shown in FIG. 8 ($\varphi\beta L$, $\beta h\ (X)$).

Using the new nonlinear function $\varphi\beta L$, $\beta h\ (X)$, expression (5) can be rewritten as the following expression (6):

$$y(m,n) = x(m,n) - \sum_{i}\sum_{j} a_{i,j} \cdot \phi_{\beta L,\beta h}\left(x(m,n) - x(m+i,n+j)\right) \qquad (6)$$

In other words, expression (6) indicates the characteristic of a new nonlinear digital filter, which uses a new nonlinear function $\varphi\beta L$, $\beta h\ (X)$ to separate and suppress only the variation component of a specific amplitude band. This will be hereinafter referred to as "specific amplitude band variation component separation type digital filter" (or

β-filter). As seen from the fact that expression (6) is derived from expression (4), the function is the same as the function provided by using two ε-filters in combination shown in FIG. 6. Therefore, one β-filter can accomplish conversion to "smooth skin" while preserving the texture of the skin in one process.

The β-filter can provide not only the suppression function of the separated specific amplitude band variation component (conversion to "smooth skin"), but also the enhancement function of the variation component ("wrinkle enhancement"). This is similar to how the expanded ε-filter is provided, by attaching the ε-filter output with the configuration of adding the small amplitude variation component separated through the ε-filter to an input image signal. Thus, as shown in FIG. 9, it is possible for one β-filter to cover high-quality conversion to "smooth skin" and "wrinkle enhancement", while considering the grain of the skin (in the previously described configuration FIG. 7, two filters of extended ε-filter I and ε-filter II are required). Therefore, an "electronic makeup apparatus" for producing natural processing results in a simple configuration can be provided.

In the basic configuration of the invented image processing apparatus using the specific amplitude band variation component separation type digital filter (or β-filter), the following two configurations are also possible: (a) "One-output type," configuration wherein one correction

output of conversion to "smooth skin," etc., is adopted. The algorithm of a specific amplitude band variation component for an input signal (subtraction or addition) is changed in response to an external correction instruction (instruction for performing "smooth skin" or "wrinkle enhancement"); and (b) "Continuously parallel output type," configuration wherein the processing results of conversion to "smooth skin" and "wrinkle enhancement" are output continuously, and either can be selected for use as required.

This is similar to the configuration example of the extended ε-filter, provided by adding the function of enhancing a small-amplitude variation component to the configuration of the conventional ε-filter.

FIGS. 10 and 11 show configuration examples of the invented image processing apparatus for executing conversion to "smooth skin" and "wrinkle enhancement" through the β-filter in the forms corresponding to (a) and (b) above. In FIGS. 10 and 11, the portion of the solid line frame indicated by numeral 4 is a specific amplitude band variation component calculation section. Each apparatus (FIG. 10, 11) also comprises a clip circuit (Clip) for suppressing the addition (common-mode addition) result of the specific amplitude band variation component for "wrinkle enhancement" to the stipulated level range of a digital image (for example, 0 to 255).

The β-filter provided by the invention will be further

discussed.

The function $\varphi\beta L, \beta h\ (X)$, which is the fundamental part of the β-filter, is characterized by the fact that it is a nonlinear function acting only on level variations having an amplitude value between the two amplitude values $\varphi\beta L$ and $\beta h\ (X)$ $(\varphi\beta L \leq |X| \leq \beta h)$, and does not involve minute variation amplitude in the proximity of 0. Both functions of the conventional ε-filter, function $\varphi\beta L, \beta h\ (X)$ and nonlinear function F (X) shown in FIG. 2, define the filter requirement in the amplitude area of level variation; the essential functional difference between both functions $\varphi\beta L, \beta h\ (X)$ and F (X) can be compared to the difference between a band-pass filter and a low-pass filter in frequency area.

In other words, the nonlinear function $\varphi\beta L, \beta h\ (X)$ is introduced, whereby producing digital filter capable of selectively separating and suppressing or enhancing only level variations contained in a specific amplitude band of an input signal sequence consisting of level variations of various amplitudes.

As previously described with reference to related previous documents, the ε-filter is a filter originally designed for the purpose of removing small-amplitude noise. For the purpose of removing noise, the function with the form as shown in FIG. 8 is not considered as the nonlinear function to be used. This is because in noise removal, it is not possible

to remove noise in one amplitude band while saving minute amplitude changes.

Therefore, the digital filter, which is defined by these nonlinear and linear functions and provided by this invention, was produced from the purpose and idea entirely different from those of previous technique. This enables new applications in each field.

Finally, by combining the use of the β filter and a color area determination circuit, image processing for executing higher-quality conversion to "smooth skin" or "wrinkle enhancement" while considering the grain of the skin and preserving peripheral details and texture is made possible. The configuration demonstrates further effectiveness as an "electronic makeup" apparatus in fields of television and movies, etc.

FIG. 12 shows a configuration example of the "electronic makeup" apparatus having such a configuration.

In FIG. 12, a color area determination circuit 5 determines a specific color area specified in parameters in an input image signal. A changeover switch 6 is controlled, based on the output of the color area determination circuit 5, so as to extract the output y (m, n) of the β filter as the output signal only in the determined color area, and output the original image signal for other areas.

As described above, the invented image processing

apparatus uses the small amplitude variation component separation function of the ε-filter and the specific amplitude band variation component separation function of the βε-filter provided by the invention to correct the input image signal sequence as a two-dimensional image. Thereby executing "wrinkle enhancement" and conversion to "smooth skin" and "wrinkle enhancement" with a more natural look. The concept of separating and weakening or enhancing the small amplitude variation component and the specific amplitude band variation component, which is the basic principle of the invention, can be applied to the processing of one-dimensional signals as so-called time-series signals, needless to say.

According to this invention, the effects of "rejuvenation" and "old age" with a natural look for video representation in television and movies, can be produced in a more natural form by image processing.

WHAT IS CLAIMED IS:

1. An image processing apparatus, named extended ε -filter, comprising:

an input section for receiving an input image;

a calculation section for calculating the small-amplitude variation component of the input image;

a signal processing section for adding the output of the calculation section to the input signal to provide a wrinkle enhanced image, and for subtracting it from the input signal to provide a smooth skin image; and

an output section for outputting both of the wrinkle enhanced image and the smooth skin image, or outputting either of the wrinkle enhanced or the smooth skin image according to the instruction from a correction instruction section.

2. The image processing apparatus as claimed in claim 1, wherein the calculation section calculates the small-amplitude variation component of the input image according to the second term of an expression (1) which is expressed by:

$$y(m,n) = x(m,n) - \sum_{i}\sum_{j} a_{i,j} \cdot F\big(x(m,n) - x(m+i,n+j)\big),$$

where

y(m,n) is the output image;

x(m,n) is the input image;

$a_{i.j}$ is a weight coefficient; and

F(x) is a nonlinear function, in which F(x)=0 when $|X|>\varepsilon_o$.

3. An image processing apparatus comprising primary and secondary ε-filter blocks and an addition section:

a primary ε-filter block including:

an input section for receiving an input image;

a calculation section for calculating the small-amplitude variation component of the input image by a small ε value, given as ε h;

a subtracting section for subtracting the small-amplitude variation component from the input image to provide a smooth skin image;

and an output section for outputting the smooth skin image;

a secondary ε-filter block including:

an input section for receiving the input image;

a calculation section for calculating the minute-amplitude variation component of the input image by a minute ε value given as ε l less than ε h;

and an output section for outputting the minute-amplitude variation component; and

the addition section for adding the output of the secondary

ε -filter block to the output of the primary block to obtain the natural looking "smooth skin" image preserving the grain and texture of the skin.

4. An image processing apparatus comprising an extended ε -filter block, an ordinary ε -filter block and a minute amplitude component adjustment section,

the extended ε -filter block, including:

an input section for receiving an input image;

a calculation section for calculating the small-amplitude variation component of the input image by a small ε value, given as ε h ;

a signal processing section for adding the output of the calculation section to the input signal to provide a wrinkle enhanced image, and for subtracting it from the input signal to provide a smooth skin image; and

an output section for outputting either of the wrinkle enhanced or the smooth skin image according to the instruction from a correction instruction section;

the second ordinary ε-filter including:

an input section for receiving the input image;

a calculation section for calculating the minute-amplitude variation component of the input image by a minute ε value given as ε l less than ε h;

and an output section for outputting the minute-amplitude variation component; and

a minute amplitude component adjustment section for adding or subtracting the secondary block's output to or from the primary block's output according to the correction instruction in order to obtain the natural looking smooth or wrinkle enhanced skin image with the grain and texture of a skin held in an original state.

5. An image processing apparatus getting arbitrarily two amplitude values as parameters, comprising:

an input section for receiving an input signal;

a calculation section for calculating selectively the variation component having the amplitude between the 2 amplitude values given as βh and βl from the input signal;

a signal processing section for adding or subtracting the variation component to or from the input signal according to the instruction from the correction instruction section in order to obtain the natural looking smooth or wrinkle enhanced skin image with the grain and texture of a skin held in an original state; and

an output section for outputting both of the smooth skin and the wrinkle enhanced image, or outputting either of them according to the instruction.

ABSTRACT OF DISCLOSURE

In this invention, for example, in order to realize conversion to "smooth skin" and "wrinkle enhancement" with a natural look while preserving the grain and texture of the skin, a specific amplitude band variation component separation type digital filter (β-filter), which comprises a specific amplitude band variation component calculation section 4, is newly provided. Further, the calculation section 4 selectively separates only a specific amplitude band variation component U (m, n) from an input image signal X (m, n) applied to the filter. An image signal y (m, n), which is provided by subtracting the component from the input image signal (conversion to "smooth skin") or by adding the component to the input image signal ("wrinkle enhancement"), is outputted in response to an external correction instruction.

FIG. 1



元信号の波形
Waveform of original signal

ε-フィルタ出力波形
ε-filter output waveform

FIG. 2



FIG. 3


2-dimensional ε-filter.
Input
x (m, n)
$\sum\sum a_{i,j} F(x(m,n) - x(m+i, n+j))$
1
+
−
Output
y (m, n) (small-amplitude noise (wrinkle) suppressed image)
(minute amplitude Noise)
u (m, n)

FIG. 4


correction Instruction Section
(Conversion to smooth skin or wrinkle enhancement)
補正指示
2
Extended ε-filter
Clip
Output
y(m, n)
(Smooth skin image or wrinkle-enhanced image)
+
- or +
Input
x(m, n)
$\sum\sum a_{i,j} F(x(m;n)-x(m+i,n+j))$
1
u(m, n)

000207 "EP0269960

FIG. 5



FIG. 6


ε - filter I
F(x)
x
εh
y1 (m, n)
(f)
+
Output
y (m, n)
(h)
Smooth skin image.
(g)
u1 (m, n)
+
u (m, n)
−
(e)
小振幅値 εh
small amplitude.
(d) ε - filter II
F(x)
x
εl
y2 (m, n)
u2 (m, n)
入力画像
input image
微小振幅値 εl
minute amplitude.

FIG. 7


minute amplitude component adjustment section
微小振幅成分調整部
3
Extended ε-filter I
F(x)
x
εh
y1(m, n) (a)
u1(m, n)
(b)
+
Output
y(m, n)
(c)
('Smooth' skin image or wrinkle-enhanced image.)
input image
ε-filter II
small amplitude εh
conversion instruction
(smooth skin or wrinkle enhancement)
F(x)
x
εL
y2(m, n)
u2(m, n)
u(m, n)
+
−
微小振幅値 εL
minute amplitude εL

FIG. 8


$\phi_{\beta L, \beta h}(x)$
βh
βL
-βh -βL
X
βL βh
-βL
-βh

FIG. 9


β-filter
inpnt image
y(m, n)
u(m, n)
βh
βL
conversion instruction

FIG. 10


conversion instruction Section.
(smooth skin or wrinkle enhancement)
β-filter
2
Output y(m, n)
(smooth skin image or wrinkle-enhanced image.)
Clip
+
- or +
Input x(m, n)
$\sum\sum a_{i,j}\phi_{\beta L\beta h}(x(m,n)-x(m+i,n+j))$
u(m, n)
4

000207 sh026960

FIG. 11



Document Suggested

FIG. 12



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:
My residence, post office address and citizenship are as stated below next to my name.
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

IMAGE PROCESSING APPARATUS

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable).
I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.
I acknowledge the duty to disclose information of which is material to the patentability as defined in 37 CFR § 1.56.
I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)			Priority Not Claimed
P. Hei. 11-298631 (Number)	Japan (Country)	20/October/1999 (Day/Month/Year Filed)	☐
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	☐
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	☐

I hereby claim the benefits under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

(Application Number)	(Filing Date)

I hereby claim the benefits under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application Number)	(Filing Date)	(Status – patented, pending, abandoned)
(Application Number)	(Filing Date)	(Status – patented, pending, abandoned)

I hereby appoint John H. Mion, Reg. No. 18,879; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562, Brian W. Hannon, Reg. No. 32,778, Abraham J. Rosner, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102, Brett S. Sylvester, Reg. No. 32,765 and Robert M. Masters, Reg. No. 35,603; my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and request that all correspondence about the application be addressed to SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC, 2100 Pennsylvania Avenue, N.W., Washington, D.C. 20037.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date October 13, 2000 First Inventor Kenji (First Name) KIRA (Last Name)

Residence Tokyo, Japan Signature Kenji KIRA

Post Office Address c/o NHK Broadcasting Center, 2-1, Jinnan 2-chome, Shibuya-ku, Tokyo 150-8001 Japan

Citizenship Japan

Date October 13, 2000 Second Inventor LEE (First Name) CHIEN HUI (Last Name)

Residence Tokyo, Japan Signature LEE CHIEN HUI

Post Office Address c/o NHK Broadcasting Center, 2-1, Jinnan 2-chome, Shibuya-ku, Tokyo 150-8001 Japan

Citizenship Japan

Date October 13, 2000 Third Inventor Teruyoshi NUMATA
First Name Last Name

Residence Tokyo, Japan Signature Teruyoshi Numata

Post Office Address c/o NHK Broadcasting Center, 2-1, Jinnan 2-chome,

Citizenship Japan Shibuya-ku, Tokyo 150-8001 Japan

Date Fourth Inventor
First Name Last Name

Residence Signature

Post Office Address

Citizenship

Date Fifth Inventor
First Name Last Name

Residence Signature

Post Office Address

Citizenship

Date Sixth Inventor
First Name Last Name

Residence Signature

Post Office Address

Citizenship

Date Seventh Inventor
First Name Last Name

Residence Signature

Post Office Address

Citizenship

Date Eighth Inventor
First Name Last Name

Residence Signature

Post Office Address

Citizenship

(Supply similar information for ninth and subsequent joint inventors.)